

PINJA W-OIL

DESCRIPTION

Water-borne modified wood oil.

PRODUCT FEATURES AND RECOMMENDED USES

- ◆ Fast drying.
- ◆ Suitable for furniture, panels, boards and other surfaces in humid premises indoors and outdoors.
- ◆ Protects the surface from moisture and dirt and prevents the growth of blue and mould.

TECHNICAL DATA

Solids content abt. 10 volume-%, 11 weight-%.

Specific gravity 1.0 kg / litre

Product code 394 6909

Theoretical coverage 1 - 2 m²/l (100 µm).
Practical coverage depends on the application method, painting conditions and the shape and roughness of the surface to be coated.

Pot life (+ 23 °C) 12 months.

Application details

Application technique	Viscosity DIN4
Dip, flow coating and brushing	delivery viscosity
Spraying	delivery viscosity

Drying times (100 - 120 g/m²)

	20 °C	50 °C
To be polished	10 - 60 min	1 - 10 min

Drying and recoating times are related to the film thickness, temperature, the relative humidity of the air and ventilation.

Thinner Water.

Cleaning of equipment Water.

Colours Clear.

PINJA W-OIL

APPLICATION DETAILS

Application	Stir the oil carefully and thin with water if necessary. To get a more even result the surface can be polished.
Application conditions	The surface to be treated must be clean and dry. During application and drying the temperature of the air, the surface to be treated and the oil has to be over 18 °C and the relative humidity of the air below 70 %.
VOC	The Volatile Organic Compounds amount to 30 ± 10 g/litre of paint.
HEALTH AND SAFETY	Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets. A health and safety data sheet is available on request from Tikkurila Coatings Oy. For professional use only.

rer120504/tmk120504/394 6909